

D-212 LINE-ARRAY FULLRANGE LOUDSPEAKER

Description

5. S Audio D - 212 is a multi-functional full range loudspeaker system with 2-way design, built into two voice coil of 12 "85 mm, equipped with a high power ultra-low distortion neodymium bass unit, with four 6"high-power of ultra-low distortion midrange unit, two 1" throat of 120 ° x20 TB-C horn, and 45mm voice coil neodymium compression driver unit. The treble and woofer is the customized unit originally imported from Europe with flexibility professional hanger. As a 2-channel system, D-212 can be either driven directly or matched with a dual-amplifier system to achieve extremely high output. Ideal for use in gymnasium, auditorium, hotel conference, theater, large - scale activities, and provide professional audio solutions.

Features

High SPL output with multi-functional full range loudspeaker system with 3-way design

1" horn unique design, customized neodymium originally imported from the European

Unique design of straight horn

12" ultra-low distortion of bass unit

Full-frequency dual channel or four channel amplifier drive

Design for use in fixed installations, auditorium, banquet hall, gymnasium and performance etc.

PARAMETERS

Type: LF/2*12" +MF/4*6" + HF/2*1" Horn

Frequency Response: LF/50Hz-4000Hz,MF/125Hz-20000Hz,HF/800Hz-20000Hz

Rated Power: LF/500W(AES) MF/120W(AES) HF/60(AES)

Impedance: 16 ohms / Pc

Dispersion HxV: 120°*10°

Sensitivity: LF/98dB(1W&1M),MF/97dB(1W&1M),HF/110dB(1W&1M)

SPL: 143dB

Crossover Frequency: active crossover

Connectors: Professional 10 core plug-in with waterproof function

Enclosure Materials: 15mm marine-grade Plywood

Enclosure Paint: Polyurea paint

Rigging: D-212 parts

Enclosure Connectors: Aluminum Profiles 212

Angle Assembly: Aluminum Profiles with adjustable angle of 0°- 8°

Plug Assembly: Φ10mm*50mm

Enclosure Cover: Black oxidized fine lines

Dimensions: 1100mm*367mm*610mm(W*H*D)

Weight: 61.8kg

