

# HX-4010 TWO-WAY FULLRANGE LOUDSPEAKER

## Technical Description

HX - 4010 is a multi-functional full range loudspeaker system with 2-way design. The loudspeaker is equipped with 90°\*60°rotating square plastic steel horn, with a 10" high power ultra-low distortion bass driver and a 1" horn compression driver unit. As a 2-way system, HX-4010 can be either driven directly or matched with a dual-amplifier system to achieve extremely high output. Ideal for use in KTV, nightclub, club, and company activities, and provide professional sound solutions.

## Features

High SPL output multi-functional full-range loudspeaker system with 2-way design  
1"horn unique design, customized driver originally imported from the European  
90°x60°rotating square plastic steel horn  
10" ultra-low distortion of bass unit  
Full-range dual channel amplifier driver  
Design for use in fixed installations, KTV, nightclub,  
near-field/midfield amplification and private club etc.

## PARAMETERS

Frequency Response: 50Hz-20kHz

Rated Power: 300W

Peak Power: 1200W

Sensitivity: 95dB

SPL: 126dB

Dispersion HxV: 90°\*60°

Crossover Frequency: 1.8kHz(passive crossover)

Impedance: 8 ohms

Connectors: 2\*Neutrik™ 1+1-

LF: 10" loudspeaker ,high power and ultra-low distortion; Voice coil:2.5" (63mm).  
Rated power: 250W (AES)

HF: 1" horn, Voice coil: 1.75"(44mm) Rated power: 50W (AES)

Enclosure Paint: Polyurea Paint (Black)

Enclosure Materials: 15mm marine-grade Birch Plywood

Dimensions: 300mm\*534mm\*340mm(W\*H\*D)

Net Weight: 16.25kg

