

# JG-2010 TWO-WAY FULLRANGE LOUDSPEAKER

## Description

JG-2010 is a multi-functional full range loudspeaker system with 2-way design. The loudspeaker is equipped with a 90°\*60°PU oval horn, with a 10" high power ultra-low distortion bass driver and a 1" horn compression driver unit. The JG-2010 speaker is designed of balance back oriented. As a 2-way system, JG-2010 can be either driven directly or matched with a dual-amplifier system to achieve extremely high output. Ideal for use in fixed installations, high-end KTV, nightclub, midfield/near-field amplification and private club etc, and provide professional sound solutions.

## Features

High SPL output multi-functional full-range loudspeaker system with 2-way design

1"horn unique design, customized driver

10" ultra-low distortion of bass unit

With the design of balance back oriented on the enclosure

90°x60° PU oval horn

Full-frequency dual channel amplifier drive

Design for use in fixed installations, KTV, nightclub, midfield/near-field amplification, and private club etc

## PARAMETERS

Frequency Response: 44Hz-20kHz

Rated Power: 300W

Peak Power: 1200W

Sensitivity: 94dB

SPL: 123dB

Dispersion HxV: 90°\*60°

Crossover Frequency: 1.8kHz(passive crossover)

Impedance: 8 ohms

Connectors: 2\*Neutrik™ 1+1-

LF: 10" loudspeaker ,high power and ultra-low distortion; Voice coil:2.5" (63mm).

Rated power: 250W (AES)

HF: 1" horn, Voice coil: 1.75"(44mm) Rated power: 50W (AES)

Enclosure Paint: Polyurea Paint (Black)

Enclosure Materials: 15mm High density MDF

Dimensions: 294mm\*540mm\*324mm(W\*H\*D)

Net Weight: 16.25kg

