

JG-2012 TWO-WAY FULLRANGE LOUDSPEAKER

Description

JG-2012 is a multi-functional full range loudspeaker system with 2-way design. The loudspeaker is equipped with a 90°*60° PU oval horn, with a 10" high power ultra-low distortion bass driver and a 1" horn compression driver unit. The JG-2012 speaker is designed of balance back oriented. As a 2-way system, JG-2012 can be either driven directly or matched with a dual-amplifier system to achieve extremely high output. Ideal for use in fixed installations, high-end KTV, nightclub, midfield/near-field amplification and private club etc, and provide professional sound solutions.

Features

High SPL output multi-functional full-range loudspeaker system with 2-way design

1"horn unique design, customized driver

12" ultra-low distortion of bass unit

With the design of balance back oriented on the enclosure

90°x60° PU oval horn

Full-frequency dual channel amplifier drive

Design for use in fixed installations, KTV, nightclub, midfield/near-field amplification, and private club etc.

PARAMETERS

Frequency Response: 42Hz-20kHz

Rated Power: 450W

Peak Power: 1800W

Sensitivity: 95dB

SPL: 126dB

Dispersion HxV: 90°*60°

Crossover Frequency: 1.8kHz(passive crossover)

Impedance: 8 ohms

Connectors: 2*Neutrik™ 1+1-

LF: 12" loudspeaker , Voice coil:3" (75mm). Rated power: 400W (AES)

HF: 1" horn, Voice coil: 1.75"(44mm) Rated power: 50W (AES)

Enclosure Paint: Polyurea Paint (Black)

Enclosure Materials: 15mm High density MDF

Dimensions: 358mm*605mm*358mm(W*H*D)

Net Weight: 21.35kg

