

Description

JS-07 is a multi-functional full range loudspeaker system with 2-way design. The loudspeaker is equipped with a 90°*60°ABS oval horn, with six 5" ultra-low distortion units and a 1" horn compression driver unit. The JS-07 speaker is designed of symmetrical trapezoidal front-oriented. As a 2-way system, JS-07 can be either driven directly or matched with a dual-amplifier system to achieve extremely high output. Ideal for use in hotels, halls, airports and conferences, and provide professional sound solutions.

Features

2-channel high SPL output with multi-functional & full-range loudspeaker system

1"horn unique design, customized driver originally imported from the European 90°x60°, ABS oval horn

5.5"ultra-low distortion of bass unit

Full-frequency dual channel amplifier drive

Design for use in fixed installations,, band, night club, near-field/midfield amplification and private club etc.

PARAMETERS

Frequency Response: 62Hz-20kHz

Rated Power: 400W

Peak Power: 1600W

Sensitivity: 95dB

SPL: 126dB

Dispersion HxV: 90°*60°

Crossover Frequency: 1.8kHz(passive crossover)

Impedance: 4 ohms

Connectors: 2*Neutrik™ 1+1-

LF: 5" loudspeaker ;Voice coil:1.2" (30mm). Rated power: 60W (AES)

HF: 1" horn, Voice coil: 1.34"(34mm) Rated power: 30W (AES)

Enclosure Paint: Polyurea Paint (Black)

Enclosure Materials: 12mm marine-grade Birch Plywood

Dimensions: 170mm*1070mm*224mm(W*H*D)

Net Weight: 17.65kg

