

SW-215B

FULLRANGE & BASS LOUDSPEAKER

Description

5.S Audio SW-215B is 2*15" compact low frequency loudspeaker with powerful ultra LF response. The design of woofer and enclosure brings out tight and accurate LF response, which is the most idea for matching with LY-12. With the most advanced units equipped with long stroke, the large magnetic brings extremely high magnetic flux to increase efficiency. The 4" voice coil is with the height of 38mm which can ensure to stroke in 26mm/pp continuous magnetic driving. The most advanced wool fiber paper corn which ensure the maximum hardness and inertial movement. The triple copper wire with the highest heat resistance is adopted to reduce the power compression when the coil is heated, and improve the sound quality and performance comprehensively.

Features

High SPL output with multi-functional & full-range loudspeaker system

Customized driver imported from the European

15"*2 ultra-low distortion of bass unit

Polyurea paint on the surface of the enclosure

Special steel mesh with thick of 2.0

Full-frequency dual channel amplifier drive

Design for use in fixed installations, KTV, nightclub, near-field/midfield amplification and private club etc.

PARAMETERS

Frequency Response: 35Hz-300Hz

Rated Power: 1400W

Peak Power: 5600W

Sensitivity: 101dB

SPL: 136dB

Dispersion HxV: -

Crossover Frequency: -

Impedance: 4 ohms

Connectors: 2*Neutrik™ 2+2-

LF: 15"*2 loudspeaker ;Voice coil:4" (100mm). Rated power:1400W (AES)

Enclosure Paint: Polyurea Paint (Black)

Enclosure Materials: 15mm marine-grade Birch Plywood

Dimensions: 1000mm*450mm*600mm(W*H*D)

Net Weight: 64.5kg

